



ProCure™ 750 UV Chamber

for use with Viper™ Pro and other SLA® systems

Conveniently post-cure large parts and/or large-capacity builds consistently and completely.



FEATURES

- Dual frequency bulbs
- Hands-free opening and closing
- Large platform turntable
- Bulb life digital display
- Auto-off function
- Exhaust port

APPLICATIONS

- Post-cure large parts and/or large-capacity builds

BENEFITS

- Achieve consistent and complete part curing
- Load and operate with ease
- Post-cure parts safely and reliably
- Optimize part properties

ProCure 750 UV Chamber

for use with Viper™ Pro and other SLA® systems

Ensure even, consistent part curing with stainless steel turntable.



Control working hours with the convenient on/off button.



Enlarge storage capacity and secure UV chamber base placement with the integrated storage unit.



Conveniently operate door with the hands-free push button.



TECHNICAL DATA

Product	ProCure 750 UV Chamber
Compatibility	All stereolithography part build volumes fitting within maximum volume capacity*
Capacity	
Door Opening (HW)	95 x 70.8 cm (37.5 x 26.875 in)
Maximum Volume Capacity (HWD)	63 x 105 x 105 cm (25 x 41.5 x 41.5 in)
Turntable	
Speed	1 RPM
Platen Diameter	105.41 cm (41.5 in)
Removable	Yes (lift off spindle)
Exhaust System	
Duct Fitting (diameter)	20.32 cm (8 in)
Power Requirements	
	110/115 VAC, 50/60 Hz, 10 A 200/240 VAC, 50/60 Hz, 6.3 A
Controls	
Power	On/Off
Working Hours (Exposure) Timer	
Hours (Elapsed Time) Meter	
Integrated Storage (HWD)	47 x 147 x 117 cm (18.5 x 58 x 46 in)
Dimensions (Uncrated)	
Height	172.7 cm (68 in)
Width	154 cm (60.8 in)
Depth (Closed)	138 cm (54.5 in)
Depth (Door Open)	264 cm (47.3 in)
Weight	
Net Weight	430 kg (950 lb)
Safety	
Automatic door interlock	
UV light-blocking window tinting	
Certifications	Pending
Warranty	One year (except bulbs)

* includes platform height.



3D Systems Corporation
26081 Avenue Hall
Valencia, CA 91355 U.S.A.

Tel: 803.326.4080
Toll-free: 800.889.2964
Fax: 803.324.8810

moreinfo@3dsystems.com
www.3dsystems.com
NASDAQ: TSDC

Warranty/Disclaimer: The performance characteristics of these products may vary according to product application, operating conditions, material combined with, or with end use. 3D Systems makes no warranties of any type, express or implied, including, but not limited to, the warranties of merchantability or fitness for a particular use.

© 2006 by 3D Systems, Inc. All rights reserved. Specifications subject to change without notice. ProCure is a trademark, and the 3D logo and SLA are registered trademarks of 3D Systems, Inc.